

ALIMPOMP/GR-oscultati

18.007.XX

IMPIEGO

Tubo in pvc superelastico con spirale acciaio.

- **Temperatura:** -10°C +60°C

STRUTTURA

- **Sottostrato:** liscio in Pvc grigio alimentare esente da Ftalati
- **Rinforzi:** spirale metallica.
- **Superficie:** liscia
- **Marchatura:** OSCULATI – SUPERFLEX/HT – SANITATION HOSE – DN 38 – Italy – lotto

APPLICATION

Superelastic Tube transparent ,smooth PVC spiral.

- **Temperature range:** -10°C +60°C

CONSTRUCTION

- **Tube:** black, smooth PVC Pthalates Free
- **Reinforcement:** steel wire helix
- **Cover:** weathering and chemicals resistant pvc
- **Branding:** OSCULATI – SUPERFLEX/HT- SANITATION HOSE – DN 38 – Italy – lotto.

DIAMETRO INTERNO INSIDE DIAMETER		SPESSORE THICKNESS		PESO TEORICO WEIGHT		PRESS.ESERCIZIO WORKING PRESSURE		ASPIRAZ. VACUUM	RAGGIO CURVATURA BENDING RADIUS		LUNGHEZZA LENGTH	
mm	inch	mm	inch	kg/mt	lbs/ft	bar	psi	bar	mm	inch	mt	ft
16	5/8"	3.2	-	0.26	0.17	5	75	0.8	35	-	60	196.8
20	3/4"	3.5	-	0.39	0.26	5	75	0.8	50	-	60	196.8
25	1"	4	-	0.52	0.35	4	75	0.8	65	-	60	196.8
30	1.3/16"	4.2	-	0.61	0.41	4	75	0.8	80	-	30	98.4
38	1.1/2"	5	-	0.80	0.53	4	60	0.8	90	-	30	98.4